

TECHNICAL SPECIFICATIONS	750	700 T	650 T	599	570	540	500
Length overall	7.54m	7.40m	6.61m	6.10m	5.80m	5.45m	5.12m
Hull length	7.40m	6.94m	6.50m	5.99m	5.70m	5.35m	5.02m
Beam	2.90m	2.76m	2.60m	2.63m	2.55m	2.43m	2.35m
Internal length	6.38m	6.40m	5.80m	5.55m	4.9m	4.59m	4.25m
Internal beam	1.57m	1.60m	1.40m	1.30m	1.19m	1.22m	1.12m
Hull deadrise	20°	21°	21°	20°	20°	20°	20°
Tube construction	1670 dtex	1670 dtex	1670 dtex	1100 dtex	1100 dtex	1100 dtex	1100 dtex
Tube Ø	42÷66cm	50÷58cm	50÷60cm	50÷60cm	50÷60cm	51÷57cm	51÷57cm
Air chambers	6	6	5	5	5	5	5
Weight	1200kg	1080kg	750kg	550kg	450kg	370kg	290kg
Person capacity	14	14	12	10	9	8	8
CE design category	C	B	C	C	C	C	C
Fuel capacity	350lt	200lt	190lt	140lt	140lt	140lt	140lt
Water capacity	80lt	55lt	50lt	50lt	50lt	50lt	50lt
Engine shaft	XXL	XL	XL	L	L	L	L
Minimum power	225hp	200hp	150hp	100hp	70hp	40hp	30hp
Maximum power	300hp	250hp	200hp	175hp	140hp	115hp	90hp

A variation of ±3% may occur in the data related to weights and measurements. Additionally, weight may vary depending on the chosen configuration. ITALBOATS Srl reserves the right to change or modify specifications at any time.